

NEW ACRS CERTIFIED PRODUCT



Introducing **NEW** Sizes
Australia/New Zealand Standard



Size for Expand Scope of Certification
In Grade 300, 300L0, 300S0, and 350

Size (AS/NZS)	Size (BS EN)	Weight	H (depth)	B (width)	T (web)	T (flange)
690 UB (125 kg/m)	UB 686x254x125	125	677.9	253.0	11.7	16.2
690 UB (140 kg/m)	UB 686x254x140	140	683.5	253.7	12.4	19.0
690 UB (152 kg/m)	UB 686x254x152	152	687.5	254.5	13.2	21.0
690 UB (170 kg/m)	UB 686x254x170	170	692.9	255.8	14.5	23.7
760 UB (134 kg/m)	UB 762x267x134	134	750.0	264.4	12.0	15.5
760 UB (147 kg/m)	UB 762x267x147	147	754.0	265.2	12.8	17.5
760 UB (173 kg/m)	UB 762x267x173	173	762.0	266.7	14.3	21.6
760 UB (197 kg/m)	UB 762x267x197	197	769.0	268.0	15.6	25.4
840 UB (176 kg/m)	UB 838x292x176	176	834.9	291.7	14.0	18.8
840 UB (194 kg/m)	UB 838x292x194	194	840.0	292.4	14.7	21.7
840 UB (226 kg/m)	UB 838x292x226	226	850.9	293.8	16.1	26.8

